

QC TRI PRO-4.8X Specifications

Motor Voltage	120 VAC, 60 Hz	
Energy Use	Hi: 555 Watts / Low: 417 Watts	
Air Flow	Hi: 4428 CFM / Low: 3436 CFM	
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 3260 CFM / Low: 2570 CFM	
dBA	Hi: 49.4 / Low: 41.6	
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 1476 SQFT to 2214 SQFT	
Minimum Attic Clearance	36"	
# of Speeds	2	
Duct Diameter	18"	
Duct Length	9 feet	
Motor Head Diameter	18 1/2"	
Motor Head Length	13 1/2"	
Dampers	Barometric Pressurized R5 Dampers	
Controls	Included: 8 Hr Electronic Timer & HI-LOW-OFF switch Optional: IT-36002 QuietCool RF Wireless Control Kit	
Warranty	15 Years	
Framing	None Required	
Joist Cutting	None Required; fits 16" or 24" on center	
Minimum Suggested Attic Venting	5.91 SQ FT net free area	
Ceiling Rough Opening	14 1/4" x 30 1/4"	
Removable Grille Outside Dimension	16" x 32"	
Shipping Weight	75 lbs.	
Box Dimensions	36" x 22" x 40"	
In The Box	-QC TRI PRO-4.8X Motorhead -Removable Grille -Cut-out Template -Window Locks	-Damper Box -9 Foot Duct -Accessory Bag -Controls



For more information visit
www.HouseFanPros.com

QC TRI PRO-4.8X
QuietCool Trident Pro Line